

**In the Claims:**

**Please amend Claim 1 as follows.**

5

1. (Currently Amended) A data processing system comprising:

a master-state data processing unit;

10 a communication bus, the master-state data processing unit exchanging asynchronous transfer mode protocol signals with the bus; and

at least one slave-state data processing unit, the slave-state data processing unit including:

a central processing unit;

15 a direct memory access unit coupled to the central processing unit, and

a Utopia mode interface unit coupled to the ~~central processing~~ direct memory access unit; the Utopia transfer mode interface unit having:

20 a processor coupled to the communication bus and exchanging asynchronous transfer mode protocol signals therewith; and

a buffer memory unit, the buffer memory unit buffering data signals between the direct memory  
25 access unit and the processor, wherein the transfer of data cells between the buffer memory unit and the direct memory interface unit is determined by an event signal.

2. (Original) The data processing system as recited in claim 1 wherein the Utopia interface unit can act in a receive mode and in a transmit mode.

5 3. (Original) The data processing system as recited in claim 1 wherein the buffer memory unit is a first-in/first-out memory unit.

4. (Original) The data processing system as  
10 recited in claim 1 wherein the processor includes:

an input interface unit; and

an output interface unit; and wherein the buffer memory unit includes:

an input buffer memory unit, wherein the transfer  
15 between the input buffer memory unit and the direct memory access unit is determined by a receive event signal; and

an output buffer memory unit, wherein the transfer between the direct memory access unit and the output  
20 buffer memory unit is determined by a transmit event signal.

5. (Original) The data processing system as recited in claim 4 wherein data is transferred from the  
25 communication bus to the input buffer memory unit, and wherein data is transferred from the output buffer memory unit to the communication unit through the output interface unit.

6. (Original) The data processing system as recited in claim 5 wherein in the input buffer memory unit and the output buffer memory units are first-  
5 in/first-out memory units.

7. (Original) The data processing system as recited in claim 4 wherein the receive event signal is generated when the buffer memory unit has a complete data  
10 cell stored therein, the receive event signal being cleared when transfer between the buffer memory unit and the direct memory access unit is begun, and wherein the transmit event signal is generated when the buffer memory unit has space for a complete data cell, the transmit  
15 event signal being cleared when the transfer of the data cell to the buffer memory unit from the direct memory access unit is begun.

**Please amend Claim 8 as follows.**

20

8. (Currently amended) A data processing system comprising:

at least one slave-state data processing unit;

a communication bus, the master-state data  
25 processing unit exchanging asynchronous transfer mode protocol signals with the bus; and

a master-state data processing unit, the master-state data processing unit including:

a central processing unit;

a direct memory access unit coupled to the  
5 central processing unit, and

a Utopia interface unit coupled to the ~~central~~  
~~processing~~ direct memory access unit; the Utopia  
interface unit having:

a processor coupled to the communication  
10 bus and exchanging asynchronous transfer mode protocol  
signals therewith; and

a buffer memory unit, the buffer memory  
unit buffering data signals between the direct memory  
access unit and the processor.

15

9. (Original) The data processing system as  
recited in claim 8 wherein the processor includes:

an input interface unit; and

an output interface unit: and wherein the buffer  
20 memory unit includes;

an input buffer memory unit; and

an output buffer memory unit.

10. (Original) The data processing system as  
25 recited in claim 9 wherein the data is transferred from  
the communication bus through the input interface unit to

the input buffer memory unit, and wherein data is transferred from the output buffer memory unit through the output interface unit to the communication bus.

5           11. (Original)       The data processing system as recited in claim 10 wherein the input buffer memory unit and the output buffer memory unit are first-in/first-out memory units.

10           12. (Original)       An Utopia interface unit for providing an interface between an external data processing unit and a direct memory access unit, the interface unit comprising:

            an input buffer memory unit, the input buffer memory  
15 unit providing data cells to the direct memory interface unit;

            an interface input unit, the interface input unit controlling the transmission of data cells from the external processing system to the input buffer memory  
20 unit;

            an output buffer memory unit, the output buffer memory unit receiving data cells from the direct memory access unit; and

            an interface output unit, the interface output unit  
25 controlling transmission of data cells from the output buffer memory unit to the external processing system.

13. (Original) The interface unit as recited in claim 12 wherein the input buffer memory unit and the output buffer memory unit are first-in/first-out memory units.

5

14. (Original) The interface unit as recited in claim 12 wherein the first-in/first-out memory units can store at least two data cells.

10 15. (Original) The interface unit as recited in claim 12 wherein data from the input buffer memory unit is transferred to the direct memory access unit in response to word-read signal from the buffer memory unit.

15 16. (Original) The interface unit as recited in claim 12 wherein data from the direct memory unit is stored in the output buffer memory unit in response to a word-write signal from the output buffer memory unit.

20 17. (Original) The interface unit as recited in claim 12 wherein data is transferred from the external processing unit to the input buffer unit in response to the cell-available signal from the input buffer unit.

25 18. (Original) The interface unit as recited in claim 12 wherein data is transferred from the output buffer memory unit to the external processing unit in

response to cell-available signal from the output buffer memory unit.

19. (Original) The interface unit as recited in  
5 claim 12 wherein the interface unit is operating in a  
slave mode, the transfer of data cells from the input  
buffer memory unit and the direct memory access unit  
being determined by a receive event signal, the transfer  
of data cells from the direct memory access unit to the  
10 output buffer memory unit being determined by a transmit  
event signal.

20. (Original) The data processing system as  
recited in claim 19 wherein the receive event signal is  
15 generated when the input buffer memory unit has a  
complete data cell stored therein, the receive event  
signal being cleared when transfer between the input  
buffer memory unit and the direct memory access unit is  
begun, and wherein the transmit event signal is generated  
20 when the output buffer memory unit has space for a  
complete data cell, the transmit event signal being  
cleared when the transfer of the data cell to the output  
buffer memory unit from the direct memory access unit is  
begun.

25